





PROJECT	SPECIFICATION SHEET	29.01.2015
REF	COMETA	
MODEL	COMETA 55052 MEDIUM BACK + HEADREST / COMETA 55152 MEDIUM BACK SPECIAL VERSION WITH FLAT ALUMINIUM BASE	
STRUCTURE	<p>SEAT: ERGONOMICALLY DESIGN SEAT WITH "WATERFALL" DESIGNED FRONT TO EASE PRESSURE UNDER THE KNEES AND PROVIDE ENHANCED COMFORT; SEAT IS MADE OF DOUBLE SHELLLED POLYPROPYLENE REINFORCED WITH FIBERGLASS; PADDED UND UPHOLSTERED;</p> <p>BACKREST AND HEADREST : CARRYING STRUCTURE OF STRONG NYLON (PA) REINFORCED WITH FIBERGLASS AND : LINKING BETWEEN SEAT AND BACKREST BY MEANS OF A METAL BRACKET.;</p> <p>BACKREST COVERED OF HEAT-WELDED NET-MEDIUM (70% POLYVINYL , 30% POLYESTER)</p>	
MECHANISM	<ul style="list-style-type: none"> SEAT/BACKREST ANGLE ADJUSTMENTS BY SYNCHRONIZED MECHANISMS WITH 5 LOCKING POSITIONS OR FREE RELAX FLOATING; OFF-CENTERED BY 100 MM; ANTISCHOCK BACKREST DEVICE FOR SOFT AND SAFE FORWARD RETURN OF THE BACKREST WHEN RELEASED TENSION CONTROL INDIVIDUALLY ADJUSTABLE FROM THE SITTING POSITION ACCORDING TO THE USER'S WEIGHT (50:120 KG). SEAT DEPTH ADJUSTEMENT BY SLIDING SEAT WITH 5 LOCKING POSITIONS HEIGHT ADJUSTABLE BACKREST BY RATCHET MECHANISM AND LOCKABLE IN SEVERAL POSITIONS DEPTH ADJUSTABLE LUMBAR SUPPORT MADE OF SOFT URETHANE FOAM HEADREST IS ADJUSTABLE IN HEIGHT AND INCLINATION 	
ARMRESTS	4D- ADJUSTABLE ARMRESTS (HEIGHT, WIDTH, DEPTH AND SWIVEL) WITH A CHROMED METAL SUPPORT AND BLACK SOFT URETHANE PADS	
SEAT HEIGHT ADJUSTMENT	SEAT HEIGHT ADJUSTMENT BY SAFETY GAS LIFT . ADJUSTING SEAT HEIGHT FROM 520 TO 650 MM OPERATED BY A LEVER INTEGRATED IN THE SYNCHRONIZED MECHANISM	
BASE	5-STAR FLAT BASE MADE OF DIE-CAST POLISHED ALUMINIUM DUAL-WHEEL CASTORS OF NYLON SUITABLE FOR SOFT FLOORS (CARPETS ETC.) , 50 MM DIAMETER.	
UPHOLSTERY	SEAT AND HEADREST CUSHIONS: SOFT AND COMFORTABLE UPHOLSTERY OF HIGH DENSITY POLYURETHANE FOAM – CFC-FREE; SEAT: FOAM DENSITY 30 KG/M3 – THICKNESS ABOUT 40MM	
COVER (SEAT ONLY)	<p>OPTION 1 : CAT B = SERIE 200 LEYFORM, 100% TREVIRA CS POLYESTER, FIRE RETARDANT FABRIC, 100.000 ABRASION CYCLES MARTINDALE;</p> <p>OPTION 2: CAT D : XTREME FABRIC FROM CAMIRA UK, FIRE RETARDANT , 100.000 ABRASION CYCLES MARTINDALE;</p> <p>OPTION 3: CAT E : CLIMATEX FABRIC (CLIMATIZED , MOISTURE REGULATING), FIRE RETARDANT, 150.000 CYCLES MARTINDALE;</p>	
CERTIFICATE	EUROPEAN STANDARD EN 1335- 1- 2- 3 TEST CERTIFICATE - 5 YEAR GUARANTEE ON THE MECHANICAL PARTS FOR A NORMAL USE AS OFFICE CHAIR, 8 HOURS PER DAY, 5 DAYS PER WEEK	
PRODUCT CERTIFICATION	EN 1335-1-2-3 (EUROPEAN OFFICIAL NORMS; LABORATORY TESTED; CERTIFICATES AVAILABLE UPON REQUEST)	
COMPANY'S CERTIFICATIONS	UNI EN ISO 9001:2000 (ISO 9001:2000) = QUALITY MANAGEMENT SYSTEM UNI EN ISO 14001:2004 (ISO 14001 :2004) = ENVIRONMENTAL MANAGEMENT SYSTEM	

Dimensions mm	COMETA - ergonomic chair	COMETA standard work chair
seat height mm	470-595	520-650
overall height mm	1225-1350	1100-1230
overall depth mm	680	680
overall width mm	680	680
seat width mm	490	490
gross weight Kg	21	18
net weight Kg	18	17,50